

LOW VOLTAGE STORAGE

IES BATT 7.68



More Usable Energy
Deep cycle DOD control



Easy Installation
Floor stand or Wall mounted



Flexible Investment
Up to 15 units per parallel



Safe & Reliable
Premium Lithium Iron Phosphate
(LFP) 6000 cycles



Quick Commissioning
One button ON/OFF,
automatic ID assignment



Perfect Compatibility
Compatible with Major
PCS Brands

Low Voltage Storage		IES-BATT-7.68
Cell Technology	LFP (LiFePO4)	
Battery Usable Energy [1]	7.68 kWh	
Nominal Voltage	51.2 V	
Operating Voltage	44.8 V - 56.16 V	
Max. Charge & Discharge Current	150 A	
COMMUNICATION		
Display	SOC Status Indicator, LED Indicator	
Communication	CAN / RS485 / RS232 / Wi-Fi	
GENERAL SPECIFICATION		
Dimension (W*D*H)	600 × 250 × 759 mm 23.6× 9.8 × 29.8 inch	
Weight	95kg (209 lbs)	
Installation	Floor Stand or Wall Mounted	
Operating Temperature [2]	Charge : 0 to 55°C (32 to 131°F) Discharge : -20 to 55°C (-4 to 131°F)	
Environmental Humidity	≤95%RH (No Condensation)	
Protection Rating	IP 20	
Cycle Life [3]	6000 Cycles or Ten (10) Years @ 80% DOD / 25°C / 0.5C, 70% EOL	
Scalability	Max 15 Batteries in Parallel	
Application	ON Grid / ON Grid + Backup / OFF grid	
STANDARD COMPLIANCE		
Compliance	UN38.3 / IEC62619 / IEC61000 (More Available Upon Request)	
COMPATIBLE PCS INVERTERS		
Brands	Deye, Sunsynk, Victron, and Solis	

[1] Test conditions: 100% depth of discharge (DOD), 0.2C rate charge & discharge at 25°C.

[2] Charge/discharge derating occurs when the operating temperature is below 0°C or above 45°C.

[3] Please refer to the Warranty Letter for applicable conditions, the warranty is due whichever comes first.