## **COMMERCIAL - R RANGE**

## **IES BATT 215R**





## Overview Indoor battery rack with IP20 protection level, inbuild lithium-ion battery and BMS



**Safe & Reliable**Self-developed 2-level / 3-level BMS,
complex protection



Easy Installation & Maintenance
Local and remote management, standard
rack and module design, front maintenance



**Quick Commissioning** Long cycle life, 8000 cycles



**Cell Balancing Technology**Advanced cell balancing



**High Density**High capacity LFP battery

High Voltage Range	IES-BATT-215R
Battery Module (Wh/V)	14.336 kWh, 51.2 V, 110 kg (242.5 lbs)
Number of Modules	15
Cell Technology	LFP (LiFePO4)
Battery Usable Energy [1]	215.04 kWh
Nominal Voltage	768.0 V
Operating Voltage	672 V - 842.4 V
Nominal Output Current	140 A / 280 A
COMMUNICATION	
Display	SOC Status Indicator, LED Indicator, LCD Display
Communication	Ethernet / CAN / RS485
GENERAL SPECFICATION	
Dimension (W*D*H)	1721 x 840 x 1776 mm   67.8 x 33.1 x 69.9 inch
Weight	1980 kg (4365 lbs)
Operating Temperature [2]	-20°C to 60°C (-4°F to 140°F)
<b>Environmental Humidity</b>	≤ 95% RH (No Condensation)
Protection Rating	IP20
Cycle Life [3]	8 000 Cycles or Ten (10) Years @ 80% DOD / 25°C / 0.5C, 70% EOL
Scalability	Version 3: 10 in Parallel Version 4: 30 in Parallel
Application	On Grid / On Grid + Backup / Off Grid
STANDARD COMPLIANCE	
Compliance	Cell: UN38.3 / IEC62619 / UL 1642 / JET

## COMPATIBLE PCS INVERTER BRANDS

**MegaRevo**: MEGA/MPS 0030 & MEGA/MPS 0050 & MEGA/MPS 0100 & MEGA/MPS 0150 & MEGA/MPS 0250 & MEGA/MPS 0500 **Atess**: PCS 500 & PCS 630 / **50kW**: Sunsynk / Deye / Solis

<sup>[1]</sup> Test conditions: 100% depth of discharge (DOD), 0.2C rate charge & discharge at 25°C.

<sup>[2]</sup> Charge/discharge derating occurs when the operating temperature from -10°C to 5°C & 45°C to 55°C.

<sup>[3]</sup> Please refer to the Warranty Letter for applicable conditions, the warranty is due whichever comes first.